

Phono Box DS2

Phono preamplifier

- Suitable for MM and MC cartridges
- Precise RIAA equalisation
- Dual mono circuitry for optimized channel separation
- Selectable input impedance on front
- Selectable input capacitance on front
- Low noise ICs
- Gold-plated RCA in & outputs
- Sandwich alu/metal casing protects from vibrations and electromagnetic interference
- Colour options: silver and black

Technical Data

Input impedance	10-47kohms
Capacitance	100/120 and 320pF
Gain	40/45/50/60/65 dB
Output voltage	500mV @ 1kHz (with 5mV input voltage @ 1kHz)
Noise floor	-80dBV
THD+N	< 0,02%
THD	0,0008%
RIAA equalisation curve accuracy	within 0,5dB/20Hz - 20kHz
Input	1 pair RCA
Output	1 pair RCA
Power supply	18V/500mA DC; 220 - 240V, 50Hz
Power consumption	100 mA DC, < 1 watt standby
Dimensions W x H x D	206 x 71 x 194 mm (alu) 240 x 72 x 194 mm (wood)
Weight	1770g without power supply



Phono preamplifier for MM/MC cartridges

Phono Box DS2 is a highly adjustable phono preamplifier suitable for all common MM and MC cartridges. With the ability to switch easily between input impedance and capacitance, as well as gain on front it becomes one of the most user friendly phono stages at this price point. It features one pair of RCA inputs for your turntable and one pair of RCA outputs which will be connected to your pre-amplifier or integrated amplifier. The casing is made of a durable aluminium metal sandwich construction, which not only will effectively protect it against electromagnetic interferences and vibrations, but will also please the eye with its simply and elegant esthaetics.

Phono Box DS2 features a very linear circuit design to deliver the best possible sound from a minimalistic PCB. With its high value sonics and low cost price it becomes an audiophile bargain!

